

## Line measurement of the referential glider including risers !

Glider

	A	L-R	Diff	Ø	Diff	Ø
1	7502	1	60		56	
2	7404	1	60		57	
3	7344	3	50	58	50	58
4	7370	1	60		67	
5	7316	-1	60		60	
6	7195	-1	42		42	
7	7093	-3	35	42	30	40
8	7046	-4	30		28	

Glider

	B	L-R
1	7446	1
2	7347	1
3	7294	-3
4	7303	-1
5	7256	-2
6	7153	0
7	7063	2
8	7018	-2

Glider

	C	L-R	Diff	Ø	Diff	Ø
1	7564	0	120		118	
2	7465	4	115		118	
3	7402	-1	105	113	108	115
4	7419	-6	110		116	
5	7330	-1	80		74	
6	7220	1	70		67	
7	7116	5	55	60	53	57
8	7053	-1	35		35	

Glider

	Stabilo	L-R
1	6753	1
2	6710	-1
3	6484	-3
4	6484	1
5	6506	0
6	6540	0
7		
8		

Left side

Glider

	A	L-R	Diff	Ø	Diff	Ø
1	7501	-1	60		56	
2	7403	-1	60		57	
3	7341	-3	50	58	44	56
4	7369	-1	60		65	
5	7317	1	60		59	
6	7196	1	42		43	
7	7096	3	35	42	35	42
8	7050	4	30		30	

Glider

	L-R	
1	7445	-1
2	7346	-1
3	7297	3
4	7304	1
5	7258	2
6	7153	0
7	7061	-2
8	7020	2

Glider

	C	L-R	Diff	Ø	Diff	Ø
1	7564	0	120		119	
2	7461	-4	115		115	
3	7403	1	105	113	106	115
4	7425	6	110		121	
5	7331	1	80		73	
6	7219	-1	70		66	
7	7111	-5	55	60	50	56
8	7054	1	35		34	

Glider

	Stabilo	L-R
1	6752	-1
2	6711	1
3	6487	3
4	6483	-1
5	6506	0
6	6540	0
7		
8		

Right side

Glider

	A	Diff	Ø	Diff	Ø
1	7502		60	56	
2	7404		60	57	
3	7343		50	47	57
4	7370		60	66	
5	7317		60	60	
6	7196		42	43	
7	7095		35	33	41
8	7048		30	29	

Glider

	B
1	7446
2	7347
3	7296
4	7304
5	7257
6	7153
7	7062
8	7019

Glider

	C	Diff	Ø	Diff	Ø
1	7564		120	119	
2	7463		115	117	
3	7403		105	107	115
4	7422		110	119	
5	7331		80	74	
6	7220		70	67	
7	7114		55	52	57
8	7054		35	35	

Glider

	Stabilo
1	6753
2	6711
3	6486
4	6484
5	6506
6	6540
7	
8	

Brakes

7635
7390
7265
7240
7130
7050
7025
7035
6980
6905
6870
6870

Recommended differences between rows

Tolerance +/- 10 mm