

Line measurement of the glider with risers



Glider: **Avax XC5 - 24**

S/N:

Right side

Center	R-L	A	A-B	Spec.	Diff
1		7332		38	
2		7301		41	
3		7273		40	
4		7288		40	
5		7232		39	
6		7204		42	
7		7171		37	
8		7187		37	
9		7174		39	
10		7104		39	
11		6981		37	
12		6972		33	
13		6899		28	
14		6890		29	

R-L	B
	7294
	7261
	7226
	7243
	7190
	7159
	7130
	7148
	7135
	7065
	6944
	6940
	6868
	6865

R-L	C	C-B	Spec.	Diff
	7370		73	
	7337		73	
	7306		75	
	7318		73	
	7265		75	
	7232		75	
	7203		75	
	7224		75	
	7204		67	
	7135		68	
	7005		57	
	6998		54	
	6914		43	
	6898		30	

R-L	Stabilo	B14-Stabilo	Spec.	Diff
	6584		280	
	6565		298	
	6472		395	
	6474		393	
	6496		372	
	6525		342	

L-R	Brakes
	7623
	7331
	7149
	7071
	6946
	6832
	6832
	6854
	6785
	6739
	6723
	6747

Left side

Center	L-R	A	A-B	Spec.	Diff
1		7332		38	
2		7301		41	
3		7273		40	
4		7288		40	
5		7232		39	
6		7204		42	
7		7171		37	
8		7187		37	
9		7174		39	
10		7104		39	
11		6981		37	
12		6972		33	
13		6899		28	
14		6890		29	

L-R	B
	7294
	7261
	7226
	7243
	7190
	7159
	7130
	7148
	7135
	7065
	6944
	6940
	6868
	6865

L-R	C	C-B	Spec.	Diff
	7370		73	
	7337		73	
	7306		75	
	7318		73	
	7265		75	
	7232		75	
	7203		75	
	7224		75	
	7204		67	
	7135		68	
	7005		57	
	6998		54	
	6914		43	
	6898		30	

L-R	Stabilo	B14-Stabilo	Spec.	Diff
	6584		280	
	6565		298	
	6472		395	
	6474		393	
	6496		372	
	6525		342	

L-R	Brakes
	7623
	7331
	7149
	7071
	6946
	6832
	6832
	6854
	6785
	6739
	6723
	6747

Total lengths were measured on the referential glider.

Tolerance: +/- 10 mm

Spec. = Recommended differences between rows

Measured by:	
Created by:	Lukas Pohl, 7.12.2016