

# Line measurement of the glider with risers



Glider: Avax XC5 - 26

S/N:

## Right side

Center	R-L	A	A-B	Spec.	Diff
1		7682		41	
2		7648		45	
3		7615		44	
4		7632		43	
5		7574		42	
6		7542		42	
7		7510		39	
8		7530		39	
9		7513		39	
10		7441		37	
11		7318		35	
12		7314		36	
13		7240		29	
14		7233		26	

R-L	B
	7642
	7603
	7572
	7589
	7533
	7501
	7472
	7491
	7474
	7404
	7284
	7278
	7212
	7208

R-L	C	C-B	Spec.	Diff
	7716		75	
	7679		76	
	7651		79	
	7666		77	
	7616		83	
	7595		95	
	7551		79	
	7570		79	
	7542		68	
	7468		64	
	7341		58	
	7336		58	
	7258		47	
	7241		34	

R-L	Stabilo	B14-Stabilo	Spec.	Diff
	6904		301	
	6888		318	
	6787		421	
	6792		418	
	6809		398	
	6844		365	

L-R	Brakes
	8046
	7766
	7542
	7522
	7337
	7280
	7213
	7296
	7196
	7184
	7131
	7185

## Left side

Center	L-R	A	A-B	Spec.	Diff
1		7682		41	
2		7648		45	
3		7615		44	
4		7632		43	
5		7574		42	
6		7542		42	
7		7510		39	
8		7530		39	
9		7513		39	
10		7441		37	
11		7318		35	
12		7314		36	
13		7240		29	
14		7233		26	

L-R	B
	7642
	7603
	7572
	7589
	7533
	7501
	7472
	7491
	7474
	7404
	7284
	7278
	7212
	7208

L-R	C	C-B	Spec.	Diff
	7716		75	
	7679		76	
	7651		79	
	7666		77	
	7616		83	
	7595		95	
	7551		79	
	7570		79	
	7542		68	
	7468		64	
	7341		58	
	7336		58	
	7258		47	
	7241		34	

L-R	Stabilo	B14-Stabilo	Spec.	Diff
	6904		301	
	6888		318	
	6787		421	
	6792		418	
	6809		398	
	6844		365	

L-R	Brakes
	8046
	7766
	7542
	7522
	7337
	7280
	7213
	7296
	7196
	7184
	7131
	7185

Total lengths were measured on the referential glider.

Tolerance: +/- 10 mm

Spec. = Recommended differences between rows

Measured by:	
Created by:	Lukas Pohl, 7.12.2016