

# Lines measurement of the test glider



gradient

Glider: **Bright5 26**

S/N: **G3826.....**

**Left side**

Center	L-R	A	A-B	Spec.	Diff	Ø	L-R	B
1	2	7032	79	76	3		-1	6953
2	2	6972	82	77	5	3	-1	6890
3	-3	6937	80	78	2		0	6857
4	2	6964	77	76	1		1	6887
5	2	6940	76	75	1		-1	6864
6	1	6896	72	73	-1	1	3	6824
7	2	6877	69	67	2		-2	6808
8	-2	6900	65	62	3		-1	6835
9	-1	6830	47	46	1		-2	6783
10	2	6778	39	37	2	3	3	6739
11	4	6709	28	21	7		1	6681
12	-2	6675	15	15	0		1	6660
13	-2	6448	-15	-12	-3		-2	6463
S	1	6296	0	0	0		1	6296

L-R	C	C-B	Spec.	Diff	Ø
-2	7027	74	79	-5	
-1	6968	78	80	-2	-2
-2	6936	79	80	-1	
-2	6968	81	79	2	
2	6942	78	78	0	
-5	6900	76	79	-3	-4
-3	6882	74	78	-4	
-4	6904	69	76	-7	
-3	6822	39	42	-3	
-3	6778	39	41	-2	0
2	6717	36	32	4	
1	6683	23	23	0	
1	6331	35	33	2	

L-R	D	D-B	Spec.	Diff	Ø
-3	7130	177	175	2	
1	7066	176	176	0	1
3	7033	176	173	3	
-1	7055	168	170	-2	
-2	7029	165	167	-2	
-2	6983	159	166	-7	-5
-1	6961	153	157	-4	
0	6980	145	151	-6	
3	6883	100	97	3	
2	6831	92	92	0	4
-1	6760	79	71	8	
4	6721	61	55	6	
4	6394	98	95	3	

Spec.	Brakes	Diff
7128	7128	0
6870	6871	1
6788	6790	2
6690	6692	2
6609	6609	0
6667	6670	3
6620	6617	-3
6630	6628	-2
6650	6649	-1

Riser: B

Glider: **Bright5 26**

S/N: **G3826.....**

**Right side**

Center	L-R	A	A-B	Spec.	Diff	Ø	L-R	B
1	-2	7030	76	76	0		1	6954
2	-2	6970	79	77	2	2	1	6891
3	3	6940	83	78	5		0	6857
4	-2	6962	76	76	0		-1	6886
5	-2	6938	73	75	-2		1	6865
6	-1	6895	74	73	1	0	-3	6821
7	-2	6875	65	67	-2		2	6810
8	2	6902	66	62	4		1	6836
9	1	6831	46	46	0		2	6785
10	-2	6776	40	37	3	3	-3	6736
11	-4	6705	25	21	4		-1	6680
12	2	6677	18	15	3		-1	6659
13	2	6450	-15	-12	-3		2	6465
S	-1	6295	0	0	0		-1	6295

L-R	C	C-B	Spec.	Diff	Ø
2	7029	75	79	-4	
1	6969	78	80	-2	0
2	6938	81	80	1	
2	6970	84	79	5	
-2	6940	75	78	-3	
5	6905	84	79	5	-1
3	6885	75	78	-3	
4	6908	72	76	-4	
3	6825	40	42	-2	
3	6781	45	41	4	1
-2	6715	35	32	3	
-1	6682	23	23	0	
-1	6330	35	33	2	

L-R	D	D-B	Spec.	Diff	Ø
3	7133	179	175	4	
-1	7065	174	176	-2	1
-3	7030	173	173	0	
1	7056	170	170	0	
2	7031	166	167	-1	
2	6985	164	166	-2	-4
1	6962	152	157	-5	
0	6980	144	151	-7	
-3	6880	95	97	-2	
-2	6829	93	92	1	3
1	6761	81	71	10	
-4	6717	58	55	3	
-4	6390	95	95	0	

Spec.	Brakes	Diff
7128	7125	-3
6870	6873	3
6788	6792	4
6690	6690	0
6609	6611	2
6667	6668	1
6620	6622	2
6630	6632	2
6650	6650	0

Riser: B

Recommended differences between rows  
Tolerance: +/- 10 mm

Measured by:  
Date: