

Lines measurement of the referential glider



gradient

Glider: **Bright5 30**

S/N: **G38301311006**

Left side

Center	L-R	A	A-B	Spec.	Diff	Ø
1	1	7678	86	82	4	
2	-1	7610	86	84	2	4
3	0	7580	89	85	4	
4	-3	7607	90	83	7	
5	2	7580	84	81	3	
6	-3	7530	80	79	1	3
7	6	7514	78	73	5	
8	4	7536	71	68	3	
9	6	7467	50	50	0	
10	6	7409	45	40	5	1
11	0	7325	22	23	-1	
12	2	7295	18	17	1	
13	0	7036	-16	-14	-2	
S	4	6878	0	0	0	

L-R	B
0	7592
-1	7524
-5	7491
-7	7517
3	7496
2	7450
2	7436
-1	7465
4	7417
1	7364
4	7303
0	7277
-1	7052
3	6878

L-R	C	C-B	Spec.	Diff	Ø
-2	7680	88	87	1	
0	7616	92	88	4	3
3	7581	90	88	2	
0	7610	93	87	6	
2	7585	89	86	3	
5	7540	90	87	3	4
1	7525	89	86	3	
3	7554	89	84	5	
-5	7454	37	46	-9	
-2	7407	43	45	-2	-2
1	7341	38	35	3	
-3	7302	25	25	0	
1	6918	40	37	3	

L-R	D	D-B	Spec.	Diff	Ø
-2	7782	190	192	-2	
-2	7719	195	193	2	2
3	7683	192	190	2	
3	7709	192	186	6	
5	7683	187	183	4	
8	7636	186	182	4	4
5	7611	175	172	3	
8	7634	169	165	4	
-1	7518	101	107	-6	
1	7466	102	101	1	2
6	7389	86	78	8	
4	7343	66	60	6	
1	6985	107	104	3	

Spec.	Brakes	Diff
7780	7778	-2
7500	7498	-2
7408	7409	1
7300	7300	0
7210	7215	5
7275	7277	2
7227	7228	1
7237	7238	1
7258	7258	0

Riser: B

Glider: **Bright5 30**

S/N: **G38301311006**

Right side

Center	L-R	A	A-B	Spec.	Diff	Ø
1	-1	7677	85	82	3	
2	1	7611	86	84	2	2
3	0	7580	84	85	-1	
4	3	7610	86	83	3	
5	-2	7578	85	81	4	
6	3	7533	85	79	6	2
7	-6	7508	74	73	1	
8	-4	7532	66	68	-2	
9	-6	7461	48	50	-2	
10	-6	7403	40	40	0	0
11	0	7325	26	23	3	
12	-2	7293	16	17	-1	
13	0	7036	-17	-14	-3	
S	-4	6874	-1	0	-1	

L-R	B
0	7592
1	7525
5	7496
7	7524
-3	7493
-2	7448
-2	7434
1	7466
-4	7413
-1	7363
-4	7299
0	7277
1	7053
-3	6875

L-R	C	C-B	Spec.	Diff	Ø
2	7682	90	87	3	
0	7616	91	88	3	0
-3	7578	82	88	-6	
0	7610	86	87	-1	
-2	7583	90	86	4	
-5	7535	87	87	0	2
-1	7524	90	86	4	
-3	7551	85	84	1	
5	7459	46	46	0	
2	7409	46	45	1	3
-1	7340	41	35	6	
3	7305	28	25	3	
-1	6917	42	37	5	

L-R	D	D-B	Spec.	Diff	Ø
2	7784	192	192	0	
2	7721	196	193	3	-2
-3	7680	184	190	-6	
-3	7706	182	186	-4	
-5	7678	185	183	2	
-8	7628	180	182	-2	-1
-5	7606	172	172	0	
-8	7626	160	165	-5	
1	7519	106	107	-1	
-1	7465	102	101	1	2
-6	7383	84	78	6	
-4	7339	62	60	2	
-1	6984	109	104	5	

Spec.	Brakes	Diff
7780	7778	-2
7500	7498	-2
7408	7409	1
7300	7300	0
7210	7215	5
7275	7277	2
7227	7228	1
7237	7238	1
7258	7258	0

Riser: B

Recommended differences between rows
Tolerance: +/- 10 mm

Measured by:
Date: