

Line measurement of the referential glider including risers !

Left side

	Glider A					
	L-R	Diff	Ø	Diff	Ø	
1	7285	5	50		52	
2	7173	0	60		64	
3	7117	-4	55	54	54	55
4	7167	-2	50		50	
5	7057	-3	50		54	
6	6942	-2	45		49	
7	6866	-6	30	38	28	39
8	6819	-4	30		29	
9	6811	-1	35		37	

	Glider B					
	L-R	Diff	Ø	Diff	Ø	
1	7233	0				
2	7109	0				
3	7063	0				
4	7117	-1				
5	7003	-1				
6	6893	0				
7	6838	0				
8	6790	4				
9	6774	3				

	Glider C					
	L-R	Diff	Ø	Diff	Ø	
1	7361	6	120		128	
2	7252	1	140		143	
3	7174	-2	105	114	111	120
4	7216	4	90		99	
5	7100	-2	90		97	
6	6979	-1	80		86	
7	6895	-1	50	52	57	56
8	6825	-3	30		35	
9	6781	1	10		7	

	Glider D	
	L-R	Diff
1	7390	2
2	7285	-1
3	7206	-3
4	7248	-2
5	7123	2
6	7004	-2
7	6904	0

	Glider Stabilo	
	L-R	Diff
1	6339	7
2	6322	3
3	6325	2
4	6346	-1

Right side

	Glider A					
	L-R	Diff	Ø	Diff	Ø	
1	7280	-5	50		47	
2	7173	0	60		64	
3	7121	4	55	54	58	55
4	7169	2	50		51	
5	7060	3	50		56	
6	6944	2	45		51	
7	6872	6	30	38	34	44
8	6823	4	30		37	
9	6812	1	35		41	

	Glider B					
	L-R	Diff	Ø	Diff	Ø	
1	7233	0				
2	7109	0				
3	7063	0				
4	7118	1				
5	7004	1				
6	6893	0				
7	6838	0				
8	6786	-4				
9	6771	-3				

	Glider C					
	L-R	Diff	Ø	Diff	Ø	
1	7355	-6	120		122	
2	7251	-1	140		142	
3	7176	2	105	114	113	118
4	7212	-4	90		94	
5	7102	2	90		98	
6	6980	1	80		87	
7	6896	1	50	52	58	59
8	6828	3	30		42	
9	6780	-1	10		9	

	Glider D	
	L-R	Diff
1	7388	-2
2	7286	1
3	7209	3
4	7250	2
5	7121	-2
6	7006	2
7	6904	0

	Glider Stabilo	
	L-R	Diff
1	6332	-7
2	6319	-3
3	6323	-2
4	6347	1

	Glider A						Glider B						Glider C						Glider D						Glider Stabilo	Brakes
	L-R	Diff	Ø	Diff	Ø	L-R	Diff	Ø	Diff	Ø	L-R	Diff	Ø	Diff	Ø	L-R	Diff	Ø	Diff	Ø	L-R	Diff	Ø			
1	7283		50		50		7233				7358		120		125		7389		150		156		6336	7310		
2	7173		60		64		7109				7252		140		143		7286		175		177		6321	7155		
3	7119		55	54	56	55	7063				7175		105	114	112	119	7208		140	148	145	152	6324	7050		
4	7168		50		51		7118				7214		90		97		7249		125		132		6347	7005		
5	7059		50		55		7004				7101		90		98		7122		110		119			6930		
6	6943		45		50		6893				6980		80		87		7005		105	92	112	99		6825		
7	6869		30	38	31	42	6838				6896		50	52	58	58	6904		60		66			6795		
8	6821		30		33		6788				6827		30		39									6805		
9	6812		35		39		6773				6781		10		8									6780		

Recommended differences between rows

Tolerance +/- 10 mm