

Line measurement of the referential glider including risers !

Left side

	Glider A				
	A	L-R	Diff	Ø	Diff
1	7931	1	60		55
2	7805	4	65		66
3	7747	2	60	60	57
4	7798	2	55		47
5	7682	-5	55		52
6	7556	-4	50		46
7	7482	0	30	40	33
8	7423	-2	30		29
9	7418	0	35		35

	Glider B	
	B	L-R
1	7876	2
2	7739	-2
3	7690	3
4	7751	3
5	7630	-2
6	7510	1
7	7449	-4
8	7394	-4
9	7383	-1

	Glider C				
	C	L-R	Diff	Ø	Diff
1	7999	-5	130		123
2	7891	1	150		152
3	7802	-3	115	123	112
4	7838	-1	95		87
5	7715	-2	85		85
6	7593	-3	85		83
7	7500	-2	50	47	51
8	7419	0	20		25
9	7372	-1	-5		-11

	Glider D				
	D	L-R	Diff	Ø	Diff
1	8037	-1	165		161
2	7933	2	190		194
3	7837	-3	150	159	147
4	7882	4	130		131
5	7755	0	120		125
6	7628	0	115	102	118
7	7520	-5	70		71

	Glider Stabulo	
	Stabulo	L-R
1	6880	1
2	6865	2
3	6866	-4
4	6893	0

Right side

	Glider A				
	A	L-R	Diff	Ø	Diff
1	7930	-1	60		56
2	7801	-4	65		60
3	7745	-2	60	60	58
4	7796	-2	55		48
5	7687	5	55		55
6	7560	4	50		51
7	7482	0	30	40	29
8	7425	2	30		27
9	7418	0	35		34

	Glider B	
	B	L-R
1	7874	-2
2	7741	2
3	7687	-3
4	7748	-3
5	7632	2
6	7509	-1
7	7453	4
8	7398	4
9	7384	1

	Glider C				
	C	L-R	Diff	Ø	Diff
1	8004	5	130		130
2	7890	-1	150		149
3	7805	3	115	123	118
4	7839	1	95		91
5	7717	2	85		85
6	7596	3	85		87
7	7502	2	50	47	49
8	7419	0	20		21
9	7373	1	-5		-11

	Glider D				
	D	L-R	Diff	Ø	Diff
1	8038	1	165		164
2	7931	-2	190		190
3	7840	3	150	159	153
4	7878	-4	130		130
5	7755	0	120		123
6	7628	0	115	102	119
7	7525	5	70		72

	Glider Stabulo	
	Stabulo	L-R
1	6879	-1
2	6863	-2
3	6870	4
4	6893	0

	Glider A					Glider B		Glider C					Glider D					Glider Stabulo		Brakes
	A	Diff	Ø	Diff	Ø	B		C	Diff	Ø	Diff	Ø	D	Diff	Ø	Diff	Ø	Stabulo		
1	7931		60		56	7875		8002		130		127		8038		165		6880	7990	
2	7803		65		63	7740		7891		150		151		7932		190		6864	7825	
3	7746		60	60	58	7689		7804		115	123	115	120	7839		150	159	6868	7710	
4	7797		55		48	7750		7839		95		89		7880		130		6893	7665	
5	7685		55		54	7631		7716		85		85		7755		120			7580	
6	7558		50		49	7510		7595		85		85		7628		115	102		7470	
7	7482		30	40	31	7451		7501		50	47	50	46	7523		70			7430	
8	7424		30		28	7396		7419		20		23							7445	
9	7418		35		35	7384		7373		-5		-11							7415	
																			7360	
																			7350	
																			7290	
																			7325	

Recommended differences between rows

Tolerance +/- 10 mm